



DTB-PCB9525UA PCB Anti-Metal Tag

Air Interface Protocol

EPC Global Class1 Gen2 ISO 18000-6C

Operational Frequency

(US Standard) 902-928 MHz

Tag Dimensions

95 * 25 * 3.5 mm



Mechanical Parameters

| | |
|---------------------|---------------------|
| Material | FR4 (PCB) |
| weight | About 18.0g / Piece |
| Thickness | 3.5 mm |
| Color | Black |
| Installation Method | Adhesive, Screws |
| Tag Dimensions | 95 * 25 mm |

Other Parameters

| | |
|-----------------------|--------------------|
| Operating Temperature | -20°C ~ 80°C |
| Storage Temperature | -30°C ~ 120°C |
| Sealing Level | IP68 |
| Certification | ROHS Certification |

Electrical Parameters

| | |
|------------------------|--|
| Air Interface Protocol | EPC Global Class1 Gen2 ISO18000-6C |
| Frequency | (US Standard) 902-928 MHz |
| IC Type | NXP UCODE 8 |
| Memory | EPC 128 bits;TID 96 bits; User Memory:No |
| IC Life | 100,000 Times |
| Data Retention | 10 Years |
| Application Surface | Metal Surface |
| Reading Range | About 5 m (US Standard, Handheld 1W) |

